




TRADE MARK

SEIKO

H-2BL-AE



SINGLE NEEDLE, LARGE HORIZONTAL AXIS HOOK, DROP FEED AND ALTERNATING PRESSERS, LOCKSTITCH MACHINE



H-2BL-AE



APPLICATIONS

For sewing medium to heavy weight materials such as fabrics, leather, vinyl, synthetics and laminated and coated products.

Suitable for sewing such products as bags, automobile work, awnings, vinyl and leather goods etc.

■ FEATURES

- Full automatic lubrication system by pump
- Large horizontal axis hook (2.0 times)
- Automatic lubricated hook
- Safety clutch prevents the hook from being damaged
- Feed regulating dial stopper assures uniform stitching
- High presser foot lift
- 3-bushings of upper feed rock shaft
- Easy adjustment of forward and reverse stitch length

■ SPECIFICATIONS

	Max. speed (s.p.m.)	Max. stitch length	Clearance under presser foot		Needle bar stroke	Needle (standard)
			(by knee)	(by hand)		
H-2BL-AE	2,000	5/16" (8 mm)	5/8" (16 mm)	5/16" (8 mm)	1-29/64" (37 mm)	DPx17 (#23) 135x17 (#160)
	Amount of lift of alternating presser foot		Bed size		Working space	
	5/64"-3/16" standard 9/64" (2 - 5 mm) standard(3.5 mm)		18-45/64" x 7" (475 x 178 mm)		10-5/16" x 5-5/16" (262 x 135 mm)	

NOTE

- (1) Speed depends on threads, materials and type of operation
 (2) Specifications subject to change without notice

■ SPECIAL PRESSER FOOT

PART NO.	TYPE OF FOOT	TYPE OF USE
B151847	Walking foot 1/4" (6.4 mm)	Foot for Piping
B151848	Walking foot 5/16" (7.9 mm)	
B151849	Walking foot 3/8" (9.5 mm)	
B151850	Presser foot	Narrow type foot for pouched products
B151851	Walking foot	
B151852	Presser foot	
BS04501	Walking foot	Reverse Foot
BS04502	Presser foot	
BS36917	Presser foot Assy. (w/Finger guard)	