



TRADE MARK

SEIKO

LPW

SINGLE NEEDLE
SERIES



**SINGLE NEEDLE, HIGH SPEED, POST BED, VERTICAL AXIS HOOK,
LOCKSTITCH MACHINES**




- Variety -

LPW-8BL

- STANDARD HOOK -



-LARGE HOOK -




LPW-6BC

Drop feed, reverse stitch,
thread trimmer



LPW-6BL

Drop feed, reverse stitch




LPW-7BC

Compound feed, reverse stitch,
thread trimmer



LPW-7BL

Compound feed, reverse stitch



LPW-8BC

Compound feed and alternating
pressers, reverse stitch, thread
trimmer



LPW-8BL

Compound feed and alternating
pressers, reverse stitch



APPLICATIONS:

For sewing medium to heavy weight fabrics, leather, vinyl, synthetics and laminated and coated materials

Suitable for sewing such as boots, shoes, gloves, luggage, handbags, awnings, covers, tents, etc.

■ FEATURES

- Post bed and wide working space makes it easy for sewing of large materials
- Semi-automatic lubrication system
- Safety clutch prevents the hook from being damaged
- Reverse stitching
- Simplified and assured thread trimming system (*)
- Compound feed and alternating pressers mechanism assures even feeding of materials (-8)
- Automatic back tack (BT) and foot lift (FL) available (*)
- Large hook version available (*)
- Two needle machines available

(*) Thread trimming machines

■ SPECIFICATIONS

Variety	Max. speed (s.p.m.)	Max. stitch length	Clearance under Presser foot		Needle bar stroke	Needle (standard)	Thread trimmer
			(by knee)	(by hand)			
-6BC	2,800	13/64" (5 mm)	5/16" (8 mm)	15/64" (6 mm)	1-5/16" (33.2 mm)	DPxF22 (#14) 134KKS (#90)	○
-7BC		11/64" (4.5 mm)	15/32" (12 mm)	21/64" (8.5 mm)		DPx17 (#18) 135x17 (#110)	
-8BC							
-6BL	2,400	7/32" (5.5 mm)	5/16" (8 mm)	9/32" (7 mm)		DPxF22 (#24) 133KKS (#180)	-
-7BL			15/32" (12 mm)	21/64" (8.5 mm)		DPx17 (#24) 135x17 (#180)	
-8BL			15/32" (12 mm)	25/64" (10 mm)			
Variety	Amount of lift of alternating presser foot		Bed size		Working space		Post height
-6BC	7/64" - 7/32" (standard 1/8") (2.7 - 5.5 mm) (standard 3.2 mm)		20-25/64" x 7" (518x177 mm)		10-5/32" x 11-11/32" (258 x 288 mm)		7" (178 mm)
-7BC							
-8BC							
-6BL	7/64" - 7/32" (standard 1/8") (2.7 - 5.5 mm) (standard 3.2 mm)						
-7BL							
-8BL							

NOTE

- (1) Speed depends on threads, materials and type of operation
- (2) Specifications subject to change without notice

