



TRADE MARK

# SEIKO

## TE / TF SERIES



**SINGLE NEEDLE, OSCILLATING SHUTTLE HOOK, CYLINDER BED, DROP FEED, LOCKSTITCH MACHINES**



TE-6



TF-6B

- Variety -



TE SERIES (RIGHT SIDE PULLEY)

TE-6

TE-6-1

For heavy duty

TE-6B

Reverse feed

Standard presser foot : Flat type  
(Roller type available)




TF SERIES (LEFT SIDE PULLEY)

TF-6

TF-6B

Reverse feed

Standard presser foot : Roller type



### APPLICATIONS:

For sewing light to medium heavy weight materials such as leather, vinyl bags, pouches, various sports equipments and other curved work, etc.

# TE / TF SERIES

## ■ FEATURES

- Long beak oscillating shuttle hook
- Cam take-up
- Cylinder bed
- Reverse stitch (TE-6B & TF-6B)
- Cloth plate for flat work available at extra charge (Part no. 8136C)

## ■ SPECIFICATIONS

Variety	Max. speed (s.p.m.)	Max. stitch length	Clearance under presser foot (by knee) (by hand)		Needle bar stroke	Needle (standard)
TE-6	1,400	15/64" (6 mm)	25/64" (10 mm)	9/32" (7 mm)	1-27/64" (36 mm)	DBx1 (#19) 16x231 (#120)
TE-6-1		13/64" (5 mm)				DBx1 (#21) 16x231 (#130)
TE-6B						DBx1 (#19) 16x231 (#120)
TF-6						TFx2 (#11) 34 LL (#75)
TF-6B		5/32" (4 mm)				
Variety	Presser foot type		Cylinder size	Working space		
	Standard	Accessories				
TE-6	flat	roller	2-27/64" (61.5 mm) dia.	11-1/32" x 5-5/16" (280 x 135 mm)		
TE-6-1	roller	flat				
TE-6B	flat	roller				
TF-6	roller	flat	2-1/2" (63.5 mm) dia.	11-1/32" x 5-33/64" (280 x 140 mm)		
TF-6B						

**NOTE**

- (1) Speed depends on threads, materials and type of operation
- (2) Specifications subject to change without notice